



SPECIFICATION SHEET

155-2-16



NOVAX RUBBER INSULATING GLOVES: CLASS 2

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- Silicone free.

APPLICATIONS

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

MAX USE VOLTAGE

	SC V rms	DC V
CLASS 2	17,000	25,500

10 NOVAX™ by G.B. INDUSTRIES
 ANSI / ASTM CLASS 2 MADE IN MALAYSIA D120 TYPE I
 MAX USE VOLT 17000V AC



TECHNICAL DATA

SHELL	Natural Rubber
COLOR	Black/Orange
CUFF STYLE	Straight, Rolled
SIZES	8-11
PACKAGING	1 pair per bag/box, 12 pair per case
CASE	21.8" x 8.7" x 3.8"
CASE WEIGHT	35.3 lbs / 16.0 kg
COO	Malaysia

BARCODES

ITEM	PAIR	CASE
155-2-16/8	01616314065650	02616314065659
155-2-16/9	01616314065643	02616314065642
155-2-16/10	01616314065667	02616314065666
155-2-16/11	01616314065674	02616314065673

DIMENSIONS (in/cm)

	8	9	10	11
A	40.6 / 16.0	40.6 / 16.0	40.6 / 16.0	40.6 / 16.0
B	3.9 / 10.0	4.1 / 10.5	4.7 / 12.0	5.3 / 13.5

Max Thickness: 2.29mm*

