

SPECIFICATION SHEET STYLE: 159-2-16



NOVAX® Class 2 Rubber Insulating Glove with Bell Cuff -16"

- ٠ Contoured shape reduces hand fatigue
- Natural rubber construction offers the required dielectric properties . combined with flexibility, strength and durability
- Bell cuff increases comfort on the job
- Silicone free
- Individually numbered for traceability and stamped with factory manufacturing date
- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection
- A WARNING: Cancer www.P65Warnings.ca.gov

Applications

- **Power Generation**
- **Electrical Contractors**
- **Plant Maintenance**
- Utility Work
- Hybrid Automotive Repair, Service and Manufacturing



Technical Data

Color	Black
Sizes Available	8-12
Packaging	Boxed
Packed	6 Pair/Case
Case Dimensions (in)	21.14 x 18.15 x 11.89
Case Weight (lbs)	14.70
Country of Origin	Malaysia
Material	Rubber
Length	16"
Cuff Color	Orange
Construction	
Certifications	NFPA 70E, ASTM D120, Silicone Free
Product Circularity	

Performance Data

Electrical Class

Class 2

Care Instructions

Wash in warm water (29°C/85°F) with mild detergent and disinfect with a small amount of chlorine bleach. Air or tumble dry at low heat (74°C/165°F). Gloves may be dusted lightly with talc to reduce tackiness. Gloves should be stored in a glove bag, finger tips up, hung and not laid flat. Leather protecting glove should be removed before storage. Never fold gloves. Store in as dry and cool (35°C/95°F maximum) location as possible, away from sources of ozone and direct sunliaht.

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2024-02-20



SKU Information

SKU	COLOR	SIZE	UPC	UPC (INNER)	UPC (CASE)
159-2-16/8	Black	8	616314094699	01616314094698	02616314094697
159-2-16/8.5	Black	8.5	616314444500	10616314444507	20616314444504
159-2-16/9	Black	9	616314094705	01616314094704	02616314094703
159-2-16/9.5	Black	9.5	616314236419	01616314236418	02616314236417
159-2-16/10	Black	10	616314094668	01616314094667	02616314094666
159-2-16/10.5	Black	10.5	616314236402	01616314236401	02616314236400
159-2-16/11	Black	11	616314094675	01616314094674	02616314094673
159-2-16/12	Black	12	616314094682	01616314094681	02616314094680

PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU® AMERICAS: +1 (800) 262-5755 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobalsafety.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED. 2024-02-20