



# SPECIFICATION SHEET

## 16-AR413



### G-TEK® POLYKOR® SEAMLESS KNIT BLENDED GLOVE WITH NEOPRENE COATED MICROSURFACE GRIP

- Seamless knit construction provides comfort without sacrificing dexterity
- Polykor® shell is lightweight, has excellent dexterity, tactile sensitivity and cut resistance while also providing protection in heat resistant applications, where sparks and minor flames are present
- Knit Wrist helps prevent dirt and debris from entering the glove
- Aramid Hem for all over protection
- Arc rating: ATPV 13 cal/cm<sup>2</sup>
- EN 407 tested Limited Flame Spread Level 4
- ASTM F1060-08 tested Contact Heat Resistance Level 2

### APPLICATIONS

- Material Handling
- Electrical
- Metal Fabrication
- Manufacturing

### CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 104°F (40°C). A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 104°F (40°C).

### TECHNICAL DATA

MATERIAL	PolyKor® Fiber, Neoprene				
COLOR	Shell: Green / Coating: Black				
GAUGE	13				
CUFF STYLE	Knit Wrist				
SIZES	S - XXL				
PACKAGING	12 pair/polybag, 6 polybag/case				
CASE	16.9" x 12.2" x 15" / 43cm x 31cm x 38cm				
CASE WEIGHT	S	M	L	XL	XXL
	15.45lbs / 7.01kg	16.84lbs / 7.64kg	18.23lbs / 8.27kg	19.91lbs / 9.03kg	21.8lbs / 9.89kg
COO	China				

### PERFORMANCE PROPERTIES

**EN388: 3X42D** ASTM F2992-15 ANSI AF Cut Level (Adopted by ANSI/ISEA 02/16)  
**EN407: 4TXXXX** EN407:2020 - Limited Flame Spread Level 4  
 ASTM F1060-08 Contact Heat Resistance Level 2

ABRASION	0	1	2	3	4	-
CUT	X	1	2	3	4	5
TEAR	0	1	2	3	4	-
PUNCTURE	0	1	2	3	4	-
CUT (TDM-100)	A	B	C	D	E	F




### BARCODES

ITEM	BAG	DOZEN	CASE
16-AR413/S	616314402289	10616314402286	20616314402283
16-AR413/M	616314402401	10616314402408	20616314402405
16-AR413/L	616314402326	10616314402323	20616314402320
16-AR413/XL	616314402364	10616314402361	20616314402368
16-AR413/XXL	616314402449	10616314402446	20616314402443

### DIMENSIONS (in/cm)

	S	M	L	XL	XXL
<b>A</b>	9.6in / 24.5cm	10in / 25.5cm	10.4in / 26.5cm	10.8in / 27.5cm	11.2 / 28.5cm
<b>B</b>	3.7in / 9.5cm	3.9in / 10cm	4.1in / 10.5cm	4.3in / 11cm	4.5in / 11.5cm
<b>H</b>	Yellow	Yellow	Yellow	Yellow	Yellow



**PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®**

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | [www.pipglobal.com](http://www.pipglobal.com)

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.