



SPECIFICATION SHEET

162-3-18



NOVAX® CLASS 2 RUBBER INSULATING GLOVES WITH CONTOUR CUFF – 18"

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection
- Contour cuff provides increased mobility and comfort
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- Silicone free

APPLICATIONS

- Power Generation
- Electrical Contractors
- Hybrid Automotive Repair/Service
- Hybrid Automobile Manufacturing
- Industrial Plant Maintenance
- Utilities

TECHNICAL DATA

MATERIAL	Natural Rubber
COLOR	Black/Red
CUFF STYLE	Contour, Rolled
SIZES	9 - 12
PACKAGING	1 pair per box, 12 pair per case
CASE DIMENSIONS	21.8" x 8.7" x 3.8" / 55.3cm x 22.1cm x 9.7cm
CASE WEIGHT	35.3 lbs / 16.0 kg
COO	Malaysia



MAX USE VOLTAGE

CLASS	AC VOLTS	DC VOLTS
3	26,500	25,500

DIMENSIONS (in/cm)

	8	9	10	11	12
A	18 / 45.7	18 / 45.7	18 / 45.7	18 / 45.7	18 / 45.7
B	3.9 / 10	4.1 / 10.5	4.7 / 12	5.3 / 13.5	5.9 / 15

Thickness: 3.5mm



BARCODES

ITEM	BOX	CASE
■ 162-3-18/9	10616314340120	20616314340127
■ 162-3-18/9.5	10616314340168	20616314340165
■ 162-3-18/10	10616314455893	20616314455890
■ 162-3-18/10.5	10616314340205	20616314340202
■ 162-3-18/11	10616314455909	20616314455906

