

SPECIFICATION SHEET 280-HP241

DYNAMIC WHISTLER CAP STYLE NON-VENTED HARD HAT WITH PIN LOCK

- Meets -ANSI/ISEA Z89.1 Type 1 and CSA Z94.1 Type 1 requirements
- Fulfills Class E Electrical Insulation requirements
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- Pin-lock adjustment system with easy to read hat sizing marks
- Precise height adjustment settings to ensure proper depth
 Low nape strap provides a secure fit, allowing the hard hat to stay
- on your head even when workers are looking down or bending over
 Non-chaffing, replaceable foam sweatband for maximum sweat
- Non-chatting, replaceable toam sweatband for maximum sweat absorption
- Shell has a rain trough for extra convenience in adverse weather conditions
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- · Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Mining
- Demolition
- High pressure jettingEnergy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA


MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE		
COLOR	□ White (-01) □ Orange (-03) □ Blue (-08) □ Red (-15) □ Yellow (-02) □ Green (-04) □ Gray (-09) □ Dark Gray (-14)		
HAT SIZE	6 - 8 (19" - 25")		
EACH WEIGHT	1.7 lbs / 0.8 kg		
PACKAGING	12 per case		
CASE	17.5" x 12.5" x 24.5" / 44.45cm x 31.75cm x 62.23cm		
CASE WEIGHT	14.5 lbs / 6.6 kg		
C00	Canada		



BARCODES

ITEM	EACH	CASE
280-HP241-01	620606000015	10620606000012
280-HP241-02	620606000022	10620606000029
280-HP241-03	620606000039	10620606000036
280-HP241-04	620606000046	10620606000043
280-HP241-08	620606000084	10620606000081
280-HP241-09	620606000091	10620606000098
280-HP241-14	620606007021	10620606007028
280-HP241-15	620606000138	10620606000135

DIMENSIONS (in)



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

968 Albany Shaker Road | Latham, NY 12110 | 800-262-5755 | 518-861-0133 | Fax: 518-861-0144 | sales@pipusa.com | www.pipusa.com

This document and the information contained herein is the property of Protective Industrial Products. Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.