

SPECIFICATION SHEET 280-HP241RV

DYNAMIC WHISTLER CAP STYLE VENTED HARD HAT WITH WHEEL RATCHET

- Meets -ANSI/ISEA Z89.1 Type 1 requirements
- Fulfills Class C electrical rating
- Vented for maximum air flow
- Lightweight shell made with UV stabilized High Density Polyethylene (HDPE) reduces worker fatigue
- 4-Point quick release suspension with strong textile straps and crown comfort pad provides a comfortable and secure fit
- SURE LOCK wheel adjustment system for one hand size adjustments
- Precise height adjustment settings to ensure proper depth
- Low nape strap provides a secure fit, allowing the hard hat to stay on your head even when workers are looking down or bending over
- Non-chaffing, replaceable foam sweatband for maximum sweat absorption
- Shell has a rain trough for extra convenience in adverse weather conditions
- Universal accessory slots accommodate a variety of eye, face and hearing protection products
- Custom logo imprinting available on all four sides of the hard hat

APPLICATIONS

- Construction
- Oil & gas
- Mining
- DemolitionHigh pressure jetting
- Energy companies
- Certain emergency services (FEMA & USAR)
- High-risk environments where high impact situations are of concern

CARE INSTRUCTIONS

The unit may be cleaned with soap and warm water and dried with a soft cloth. The helmet should not be cleaned with chemical or abrasive cleaners. The helmet should be stored out of direct sunlight, away from chemicals and not exposed to extremes of temperature.

TECHNICAL DATA

MATERIAL	Shell: High Density Polyethylene, Recyclable Suspension: 4 point quick release clips, nylon strap and crown protection pad Sweatband: Foam PE		
COLOR	□ White (-01) ■ Orange (-03) ■ Blue (-08) ■ Red (-15) ■ Yellow (-02) ■ Green (-04) ■ Gray (-09) ■ Dark Gray (-14)		
HAT SIZE	6 - 8 (19" - 25")		
EACH WEIGHT	1.7 lbs / 0.8 kg		
PACKAGING	12 per case		
CASE	17.5" x 12.5" x 24.5" / 44.45cm x 31.75cm x 62.23cm		
CASE WEIGHT	14.5 lbs / 6.6 kg		
C00	Canada		



BARCODES

DAIK G G D L G			
ITEM	EACH	CASE	
☐ 280-HP241RV-01	620606006376	10620606006373	
280-HP241RV-02	620606006383	10620606006380	
280-HP241RV-03	620606006390	10620606006397	
280-HP241RV-04	620606006406	10620606006403	
280-HP241RV-08	620606006444	10620606006441	
280-HP241RV-09	620606006451	10620606006458	
280-HP241RV-14	620606006505	10620606006502	
280-HP241RV-15	620606006512	10620606006519	

DIMENSIONS (in)

