



SPECIFICATION SHEET

CCNCHR-62RB-5PK

AUTO GRID ROYAL BLUE COVERALL

- ESD safe
- Raglan Sleeves for more movement
- Extra Wide Front Facing with Double Pull Zipper to protect clothing worn under coveralls
- Inside left breast pocket and back hip pocket with flap to carry essentials
- Hidden Snaps and Tabs on Inside Back Waist for additional sizing
- Black Tricot vents on full upper back, sleeve outseam, leg inseam and leg back to allow for maximum breathability
- Elastic sleeve opening with hidden snap closure for easy donning
- Pass through pockets side front with inside (modesty) flap
- Radio webbing loops on front sleeve seams and back right waist to hang tools
- Reusable clothing that will withstand 50-100 washings

APPLICATIONS

- Paint/Spray
- Powder Coating

CARE INSTRUCTIONS

Make sure all zippers are closed. Use less harsh soap (milk alkaline or neutral soaps) or detergents. Wash at 120°F for colors and 140°F for whites. Rinse cold. No bleach. Tumble dry moderate (1400F). After drying tumble dry cold for 5 minutes. No iron. **Our garments do to not come wearer ready- meaning they need to be laundered before an employee wears them in an ISO class cleanroom.**

TECHNICAL DATA

| | | | | |
|--|--|----------------------|----------------------|----------------------|
| MATERIAL | 99% Cotton 1% Carton | | | |
| COLOR | ■ Royal Blue | | | |
| SIZES | S-3XL | | | |
| PACKAGING | 5 PACK (sizes S-XL) 2XL and 3XL sold as EACH | | | |
| COO | China | | | |
| | | 1X | 5X | 10X |
| SURFACE RESISTIVITY (OHMS/UNIT ²) | AATCC 76 | 2.40x10 ⁷ | 1.70x10 ⁷ | 4.14x10 ⁸ |
| STATIC DECAY (5000 TO 500 VOLTS, SEC) | FTMS 4046-101C | <0.01 | <0.01 | <0.01 |
| AIR POROSITY (FT ³ /MINUTES/FT ²) | ASTM D737 | 16.8 | 17.5 | 20.15 |
| WATER VAPOR TRANSMISSION (G/M ² /24H) | ASTM E96 (D) | 1363 | 1520 | 1380 |


BARCODES

| ITEM | EACH | BOX | CASE |
|-----------------------|--------------|----------------|----------------|
| ■ CCNCHR-62RB-5PK-S | 616314455247 | 10616314455244 | 20616314455241 |
| ■ CCNCHR-62RB-5PK-M | 616314455254 | 10616314455251 | 20616314455258 |
| ■ CCNCHR-62RB-5PK-L | 616314455261 | 10616314455268 | 20616314455265 |
| ■ CCNCHR-62RB-5PK-XL | 616314455278 | 10616314455275 | 20616314455272 |
| ■ CCNCHR-62RB-5PK-2XL | 616314455285 | 10616314455282 | 20616314455289 |
| ■ CCNCHR-62RB-5PK-3XL | 616314455292 | 10616314455299 | 20616314455296 |



DIMENSIONS (in/cm)

| | S | M | L | XL | 2XL | 3XL |
|----------|-----------|-----------|-----------|------------|-----------|-----------|
| A | 17.3 / 44 | 18.8 / 48 | 20.4 / 52 | 22.04 / 56 | 23.6 / 60 | 25.1 / 64 |
| B | 14.9 / 38 | 16.5 / 42 | 18.1 / 46 | 19.6 / 50 | 21.2 / 54 | 22.8 / 58 |
| C | 26.3 / 67 | 27.5 / 70 | 28.7 / 73 | 29.9 / 76 | 31.1 / 79 | 32.2 / 82 |
| D | 13.3 / 34 | 13.7 / 35 | 14.1 / 36 | 14.5 / 37 | 14.9 / 38 | 15.3 / 39 |
| E | 11.8 / 30 | 11.8 / 30 | 11.8 / 30 | 11.8 / 30 | 11.8 / 30 | 11.8 / 30 |



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.