





STANDARD SPECIFICATIONS

| Model/Size (lbs) | 20 | 28 | 33.5 | 43.5 |
|---------------------------|-----------|-----------|-----------|-----------|
| Height (in) | 20.3 | 24.8 | 28 | 33.7 |
| LPG Capacity (gal) | 4.7 | 6.8 | 7.9 | 10.3 |
| Water Capacity (lbs) | 47.6 | 67.9 | 80 | 103.6 |
| Nominal Tare Weight (lbs) | 19.3 | 19.5 | 22.9 | 27 |
| Cylinder Diameter (in) | 12.3 | 12.3 | 12.3 | 12.3 |
| Cylinder Volume (cu. in) | 1,318 | 1,883 | 2,214 | 2,868 |
| Collar Diameter (in) | 10.8 | 10.8 | 10.8 | 10.8 |
| Collar Height (in) | 6.8 | 6.8 | 6.8 | 6.8 |
| Footring Diameter (in) | 9.4 | 9.4 | 9.4 | 9.4 |
| Standard Specification | DOT-4E240 | DOT-4E240 | DOT-4E240 | DOT-4E240 |

METRIC SPECIFICATIONS

| Model/Size (lbs) | 20 | 28 | 33.5 | 43.5 |
|--------------------------|-----------|-----------|-----------|-----------|
| Height (mm) | 516 | 2699 | 711 | 855 |
| LPG Capacity (l) | 17.8 | 25.7 | 29.9 | 39 |
| Water Capacity (kg) | 21.6 | 30.8 | 36.3 | 47 |
| Nominal Tare Weight (kg) | 8.8 | 8.8 | 10.4 | 12.2 |
| Cylinder Diameter (mm) | 312 | 312 | 312 | 312 |
| Cylinder Volume (l) | 21.6 | 30.8 | 36.3 | 47 |
| Collar Diameter (mm) | 274 | 274 | 274 | 274 |
| Collar Height (mm) | 173 | 173 | 173 | 173 |
| Footring Diameter (mm) | 238 | 238 | 238 | 238 |
| Standard Specification | DOT-4E240 | DOT-4E240 | DOT-4E240 | DOT-4E240 |

All dimensions are approximate



- A. Float gauge (float shown; exterior read-out not visible)
- B. Liquid fill valve
- C. Vapor withdrawal tube/valve (aluminum = non-rusting)
-Optional opening
- D. Liquid withdrawal tube/valve (aluminum = non-rusting)
- E. Fixed liquid level
- F. Safety relief valve

Deep, heavy-duty footring provides the largest clearance in the industry. Cylinders are stackable.