

## INNOVATIVE TECHNOLOGY DESIGNED TO MAKE TANK MONITORING EASIER THAN EVER.

Featuring Otodata's state-of-the-art monitoring technology protected by a durable lid, SmartLid is the cutting-edge integrated lid and tank monitor solution that keeps service calls to an absolute minimum.



# SMARTLID<sup>®</sup>

### EASY TO INSTALL.

The lid arrives with the monitor pre-activated, making installation in the field quick and easy with no tools needed.

### EASY TO USE.

With a strong signal, long battery life and a convenient user-friendly app, you'll never be far from the accurate tank level information you need.

### EASY TO SELL.

SmartLid will transform your Worthington Industries vertical and horizontal tanks in ways that will boost sales and separate yourself from competition.



## SMARTLID® MAKES TANK MONITORING EASIER AND MORE RELIABLE

Featuring Otodata®'s technology in our durable design, this integrated lid and tank monitor is easy to install and offers reliable monitoring that will keep your service calls to an absolute minimum.

# SMARTLID®

### EASY TO INSTALL.

The lid arrives with the monitor pre-activated, making installation in the field quick and easy with no tools needed.

### EASY TO USE.

With a strong signal, long battery life and a convenient user-friendly app, you'll never be far from the accurate tank level information you need.

### EASY TO SELL.

SmartLid will transform your Worthington Industries vertical and horizontal tanks in ways that will boost sales and separate yourself from competition.



# LESS GUESSWORK. LESS SERVICE CALLS. LESS SERVICE CALLS.

The integrated lid and tank monitor created with you in mind.



## FEATURES

- Waterproof polypropylene casing
- Long-lasting lithium thionyl chloride battery with super capacitor
- Monitor positioned to ensure strongest signal
- Fits the Worthington 420-pound heating tank with 16-inch collar

## PUT A LID ON UNNECESSARY SERVICE TRIPS

- Longest battery life in the industry
- Dual SIM and LTE technology for maximum coverage
- Automatic network updates for easier management
- Unlimited reports and alerts
- An app delivering real-time gas level data



## SMARTLID SPECS

	Standard	Metric
Dimensions	19.7 in x 16.6 in x 5.4 in	500.38 mm x 421.64 mm x 137.16 mm
Lid Weight	3 lbs	1.6 kg
Cellular Technology	Dual SIM, LTE, CAT-M	Dual SIM with CAT-M and NB-IoT
Sensor & Gauge Input	Level	Level
Power Inputs	Hybrid LTC 7.2 VDC, LTC 3.6 VDC	Hybrid LTC 7.2 VDC, LTC 3.6 VDC
Battery life	~ 15 years	~ 15 years
Reporting Schedule	Unlimited, configurable	Unlimited, configurable
Material	Polypropylene	Polypropylene
Operating Temperature Range	-22 F to 140 F	-40 C to 60 C